

LAYAR LED LUAR RUANG

Microvision
Realizing Your Full Idea

Microvision
MVI HL FCO - 6.0
FULL CABINET OUTDOOR

Pilihan Terbaik Untuk
Media Digital Luar Ruang



KECERAHAN TINGGI



BERBAGAI CARA
PEMASANGAN



TAHAN LAMA

FCO
FULL CABINET OUTDOOR

Fix installation, menggunakan kabinet dengan penutup di bagian belakang

Aplikasi :

Periklanan, Pusat Swalayan, Lapangan Olahraga, Stadion, Penunjuk jalan, dll

SPECIFICATION**MVI HL FCO - 6.0**

Pixel Pitch	6 mm
Module size	192*192mm
Pixel density	27777dots/m ²
LED lamp	SMD3535
Module resolution	32*32
Viewing distance	6-160M
Max power consumption	1050W/m ²
Standard cabinet size	960*960mm
Drive mode	1/8scan
Brightness	>5000cd/m ²
Frame frequency	60Hz/s
Refresh rate	1920Hz/s
Life time	>100,000 hours
Defect rate	<0.0001
Temperature range storage	-20-65°C
Temperature range working	-20 to 50°C
Gray scale/color	4096 grades for R, G and B
Working voltage	110/220V/AC
Viewing angle horizontal	120°
Viewing angle vertical	120°"
Display content	videos, pictures and graphics
Operating humidity	10-95%
Storage humidity	10-95%

* data diatas dapat berubah tanpa pemberitahuan sebelumnya