


LAYAR LED LUAR RUANG

**Microvision**  
Realizing Your Full Idea

**Microvision**  
**MVI CFCO HL 10**  
FULL CABINET OUTDOOR

Pilihan Terbaik Untuk  
Media Digital Luar Ruang



KECERAHAN TINGGI



BERBAGAI CARA  
PEMASANGAN



TAHAN LAMA

**CFCO**  
FULL CABINET OUTDOOR

Fix installation, menggunakan kabinet dengan penutup di bagian belakang

**Aplikasi :**

Periklanan, Pusat Swalayan, Lapangan Olahraga, Stadion, Penunjuk jalan, dll

<b>SPECIFICATION</b>	<b>MVI CFCO HL 10</b>
<b>Pixel Pitch</b>	10 mm
<b>Module size WxHxD</b>	320*160*17 mm
<b>Pixel density</b>	10000 dots/m <sup>2</sup>
<b>LED lamp</b>	SMD3535
<b>Module resolution</b>	32*16
<b>Viewing distance</b>	10-100 m
<b>Max power consumption</b>	1100 W/m <sup>2</sup>
<b>Standard cabinet size WxHxD (only cabinet)</b>	960*960*140 mm
<b>Drive mode</b>	1/2 scan
<b>Brightness</b>	5500-6000 cd/m <sup>2</sup>
<b>Frame frequency</b>	≥60 Hz/s
<b>Refresh rate</b>	≥960 Hz/s
<b>Life time</b>	>100,000 hours
<b>Defect rate</b>	<0.0001
<b>Temperature range storage</b>	-20 to 65°C
<b>Temperature range working</b>	-20 to 50°C
<b>Gray scale/color</b>	4096 grades for R ,G and B
<b>Working voltage</b>	110/220V AC
<b>Viewing angle horizontal</b>	120°
<b>Viewing angle vertical</b>	120°
<b>Display content</b>	videos, pictures and graphics
<b>Operating humidity</b>	10-95%
<b>Storage humidity</b>	10-95%
<b>Panel Weight kg/sqm (full assembled)</b>	55
<b>IP Rating</b>	IP65
<b>Module Maintenance (front/rear)</b>	rear
<b>PSU &amp; others maintenance (front/rear)</b>	rear

\* data diatas dapat berubah tanpa pemberitahuan sebelumnya