


LAYAR LED LUAR RUANG

Microvision
Realizing Your Full Idea

Microvision
MVI CFCO HL
FULL CABINET OUTDOOR

Pilihan Terbaik Untuk
Media Digital Luar Ruang



KECERAHAN TINGGI



BERBAGAI CARA
PEMASANGAN



TAHAN LAMA

CFCO
FULL CABINET OUTDOOR

Fix installation, menggunakan kabinet dengan penutup di bagian belakang

Aplikasi :

Periklanan, Pusat Swalayan, Lapangan Olahraga, Stadion, Penunjuk jalan, dll

SPECIFICATION	P4	P5	P6	P8	P10
Pixel Pitch (mm)	4	5	6	8	10
Module size WxHxD	256*128*15 mm	160*160*16 mm	192*192*16.5 mm	256*128*17 mm	320*160*17 mm
Pixel density	62500 dots/m ²	40000 dots/m ²	27777 dots/m ²	15625 dots/m ²	10000 dots/m ²
LED lamp	SMD1921	SMD2727	SMD3535	SMD3535	SMD3535
Module resolution	64*32	32*32	32*32	32*16	32*16
Viewing distance	>4 m	5-35 m	6-160 m	8-80 m	10-100 m
Max power consumption	1100 W/m ²	1200 W/m ²	1200 W/m ²	1200 W/m ²	1100 W/m ²
Standard cabinet size WxHxD (only cabinet)	768*768*140 mm	640*640*140 mm	960*960*140 mm	1024*1024*140 mm	960*960*140 mm
Drive mode	1/8 scan	1/8 scan	1/8 scan	1/4 scan	1/2 scan
Brightness	6000-6500 cd/m ²	5500-6000 cd/m ²	5500-6000 cd/m ²	5500-6000 cd/m ²	5500-6000 cd/m ²
Frame frequency	≥60 Hz/s	≥60 Hz/s	≥60 Hz/s	≥60 Hz/s	≥60 Hz/s
Refresh rate	≥960 Hz/s	≥960 Hz/s	≥960 Hz/s	≥960 Hz/s	≥960 Hz/s
Life time	>100,000 hours	>50,000 hours	>100,000 hours	>100,000 hours	>100,000 hours
Defect rate	<0.0001	<0.0001	<0.0001	<0.0001	<0.0001
Temperature range storage	-20 to 65°C	-20 to 65°C	-20 to 65°C	-20 to 65°C	-20 to 65°C
Temperature range working	-20 to 50°C	-20 to 50°C	-20 to 50°C	-20 to 50°C	-20 to 50°C
Gray scale/color	4096 grades for R, G and B	4096 grades for R, G and B	4096 grades for R, G and B	4096 grades for R, G and B	4096 grades for R, G and B
Working voltage	110/220V AC	110/220V AC	110/220V AC	110/220V AC	110/220V AC
Viewing angle horizontal	120°	120°	120°	120°	120°
Viewing angle vertical	120°	120°	120°	120°	120°
Display content	videos, pictures and graphics	videos, pictures and graphics	videos, pictures and graphics	videos, pictures and graphics	videos, pictures and graphics
Operating humidity	10-95%	10-95%	10-95%	10-95%	10-95%
Storage humidity	10-95%	10-95%	10-95%	10-95%	10-95%
Panel Weight kg/sqm (full assembled)	40	45	45	50	55
IP Rating	IP65	IP65	IP65	IP65	IP65
Module Maintenance (front/rear)	rear	rear	rear	rear	rear
PSU & others maintenance (front/rear)	rear	rear	rear	rear	rear

* data diatas dapat berubah tanpa pemberitahuan sebelumnya