

LAYAR LED DALAM RUANG


Microvision
Realizing Your Full Idea

Microvision

MVI MDLI HL 03

MODULAR INDOOR

Pilihan Terbaik Untuk
Media Digital Dalam Ruang



KECERAHAN TINGGI



BERBAGAI CARA
PEMASANGAN



TAHAN LAMA

MDLI MODULAR INDOOR

Model fix installation, modul langsung dipasang pada bracket atau konstruksi LED display



Aplikasi :

Auditorium, Lobi, Ruang Kontrol, Ruang Rapat, Ruang Serbaguna, Ruang Galeri, Tempat Ibadah, Retail, Dll.

SPECIFICATION**MVI MDLI HL 03**

Pixel Pitch	3 mm
Module size WxHxD	192*192*16 mm
Pixel density	111111 dots/m ²
LED lamp	SMD2121
Module resolution	64*64
Viewing distance	3-25 m
Max power consumption	1050 W/m ²
Drive mode	1/32 scan
Brightness	1200-1500 cd/m ²
Frame frequency	≥60 Hz/s
Refresh rate	360-1920 Hz/s
Life time	>100,000 hours
Defect rate	<0.0001
Temperature range storage	-20 to 65°C
Temperature range working	-20 to 50°C
Gray scale/color	4096 grades for R ,G and B
Working voltage	110/220V AC
Viewing angle horizontal	120°
Viewing angle vertical	120°
Display content	videos, pictures and graphics
Operating humidity	10-90%
Storage humidity	10-90%
Module Maintenance (front/rear)	front
PSU & others maintenance (front/rear)	front

* data diatas dapat berubah tanpa pemberitahuan sebelumnya